

PANTHER LS8E

NEW!

PANTHER™ LS8E Hand-Held Thermal Transfer Printer and Accessories

The versatile *PANTHER™* LS8E Hand-Held Thermal Transfer Printer with label cut-to-length functionality eliminates label waste and label trimming labor. A partial cut feature is available to provide tear-apart strips of labels for quicker installation.

The *PANTHER™* LS8E Hand-Held Thermal Transfer Printer prints high quality, industrial labels on a wide variety of materials for electrical and network applications such as wire/cable, components, safety, and facility identification. The printer uses label cassettes that contain an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in cassette. The fast loading label cassettes include both label material and ribbon to make changing labels easy.

The compact and rugged *PANTHER™* LS8E is easy to use and fits comfortably in one hand. The large, backlit display makes the *PANTHER™* LS8E the ideal tool for printing labels at a remote job site. USB interface for importing data, system upgrades, and printing labels from a wireless laptop or desktop computer.



Key Features

Benefits

Label cut-to-length functionality	Eliminates label waste and label trimming labor
Unique cutter design allows full or partial label cutting	Flexibility to choose individually cut labels or a strip of tear-apart labels for quicker installation
Cassettes with automatic label recognition	Label cassettes contain an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in cassette
Market specific labeling tools	Simplify label creation for network components, panel building, and construction and maintenance
USB interface	Allows importing data, system upgrades, and printing labels from a wireless laptop or desktop computer
Print self-laminating labels, heat shrink tubing, die-cut component labels and continuous tape	One printer for all labeling applications Printed labels withstand harsh operating conditions including abrasion, chemicals, and temperature exposure
Fast loading label cassette	Contains both label material and ribbon to make changing labels easy
Large graphic display with backlight	Maximize label design area with backlight for improved visibility
Compact, rugged design	Easy to use and fits comfortably in one hand
Crisp thermal transfer print	High quality print enhances label appearance

Ordering Information – Printer and Accessories



LS8E-KIT



LS8E

Part Number	Part Description	Std. Pkg. Qty.
LS8E-KIT	Includes LS8E printer, one cassette of S100X150VAC self-laminating labels, six AA alkaline batteries, LS8-CASE, LS8-PCKIT, LS8-IB, LS8-WS, quick reference card and operator's manual.	1
LS8E	Includes LS8E printer, one cassette of S100X150VAC self-laminating labels, six AA alkaline batteries and quick reference card.	1
LS8E-ACS*	120 VAC power adapter for North America.	1
LS8-CASE	Rigid carrying case.	1
LS8-PCKIT	Includes USB cable and PC interface software for importing data, system upgrades, or printing from a wireless laptop or desktop computer.	1
LS8-IB	Protective impact bumper.	1
LS8-WS	Wrist strap.	1
LS8-CLN	Cleaning kit.	1

*Cannot be used to charge batteries.
Other adapters available, replace S with A (Australia), C (China), E (Europe) and U (UK).

PC Interface

Connect the PANTHER™ LS8E printer to a wireless laptop or desktop computer for importing data, system upgrades, and printing labels.



USB compatible

- Download and print label files from MICROSOFT EXCEL^
- Archive label files on a computer for later use or sharing
- Install LS8E operating system upgrades
- Print labels directly from PANDUIT® EASY-MARK™ Labeling Software
- LS8-PCKIT includes a USB cable and CD-ROM with software and operator's manual

^EXCEL is a registered trademark of Microsoft Corporation in the United States and/or other countries.

Label Design Flexibility

- Label cut-to-length functionality eliminates label waste and label trimming labor
- Partial cut feature available to provide tear-apart strips of labels
- Large graphic display with backlight for improved visibility
- User interface available in English, French, German, Italian, Spanish and Portuguese
- Market specific labeling tools simplify label creation for network components, panel building, and construction and maintenance
- Customize your labels with these advanced features:
 - Alpha and numeric serialization
 - Bar codes
 - Symbols
 - Date and time stamp
 - Lines
 - Frames
 - Data lists




Cut-to-Length Labels



Partial cut strip of labels




Graphic display with backlight



Customize labels with advanced features

Self-Laminating Label Cassettes




- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Self-laminating adhesive labels for wire/cable identification include a colored print-on area and clear overlamine

Part Number	Part Description	Width		Length		Print-On Height		Min. Cable O.D.		Max. Cable O.D.		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm		
S050X075VAC	White print-on area, vinyl label for 18 – 14 AWG wires, 450/cassette.	.50	12.70	.75	19.05	.25	6.35	.08	2.02	.16	4.04	1	10
S050X125VAC	White print-on area, vinyl label for 12 – 10 AWG wires, 225/cassette.	.50	12.70	1.25	31.75	.38	9.65	.12	3.07	.28	7.03	1	10
S050X150VAC	White print-on area, vinyl label for Cat. 5e/Cat. 6 cables, 200/cassette.	.50	12.70	1.50	38.10	.50	12.70	.16	4.04	.32	8.09	1	10
S075X075VAC	White print-on area, vinyl label for 18 – 14 AWG wires, 350/cassette.	.75	19.05	.75	19.05	.25	6.35	.08	2.02	.16	4.04	1	10
S075X100VAC	White print-on area, vinyl label for 12 – 10 AWG wires, 275/cassette.	.75	19.05	1.00	25.40	.38	9.65	.12	3.05	.20	5.08	1	10
S075X125VAC	White print-on area, vinyl label for 12 – 10 AWG wires, 225/cassette.	.75	19.05	1.25	31.75	.38	9.65	.12	3.07	.28	7.03	1	10
S075X150VAC	White print-on area, vinyl label for Cat. 5e/Cat. 6 cables, 200/cassette.	.75	19.05	1.50	38.10	.50	12.70	.16	4.04	.32	8.09	1	10
S100X075VAC	White print-on area, vinyl label for 18 – 14 AWG wires, 350/cassette.	1.00	25.40	.75	19.05	.25	6.35	.08	2.02	.16	4.04	1	10
S100X125VAC	White print-on area, vinyl label for 12 – 10 AWG wires, 225/cassette.	1.00	25.40	1.25	31.75	.38	9.65	.12	3.07	.28	7.03	1	10
S100X150VAC‡	White print-on area, vinyl label for Cat. 5e/Cat. 6 cables, 200/cassette.	1.00	25.40	1.50	38.10	.50	12.70	.16	4.04	.32	8.09	1	10
S100X225VAC‡	White print-on area, vinyl label for 8 – 4 AWG wires, 125/cassette.	1.00	25.40	2.25	57.15	.75	19.05	.24	6.06	.48	12.19	1	10
S100X400VAC	White print-on area, vinyl label for 2 – 1 AWG wires, 75/cassette.	1.00	25.40	4.00	101.60	1.00	25.40	.32	8.09	.95	24.26	1	10
S100X650VAC	White print-on area, vinyl label for 1/0-250 MCM wires, 50/cassette.	1.00	25.40	6.50	165.10	1.50	38.10	.48	12.19	1.59	40.39	1	10


‡Other colors available, replace A with B (Blue), D (Green), H (Red) and I (Yellow).
Order number of cassettes required.

LABELCORE™ Fiber Optic Cable Identification System


- Provides a larger labeling surface on small fiber cables and allows legends to be clearly seen
- Sleeve is made of flexible PVC material
- Locate sleeve on straight section of cable at least 2 inches from fiber boot



Apply LABELCORE™ sleeve to cable



Wrap self-laminating label around LABELCORE™ sleeve



LABELCORE™ sleeves labeled and installed

Part Number	Description	Std. Pkg. Qty.	Std. Ctn. Qty.
NWSLC-2Y	Yellow, cable identification sleeve, 2mm simplex cable.	100	1000
NWSLC-3Y	Orange, cable identification sleeve, 3mm simplex cable.	100	1000
NWSLC-7Y	White, cable identification sleeve, 3mm duplex fiber cable.	100	1000

Order number of sleeves required.

Self-Laminating Label Cassettes for Use with LABELCORE™ Fiber Optic Cable Identification System

Part Number	Description	Width		Length		Print-On Height		Min. Cable O.D.		Max. Cable O.D.		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm	In.	mm		
S100X160VAC	White print-on, self-laminating vinyl label 175/cassette. For use with NWSLC-2Y and NWSLC-3Y.	1.00	25.40	1.60	40.64	.80	20.32	.25	6.35	.25	6.35	1	10
S100X220VAC	White print-on, self-laminating vinyl label 125/cassette. For use with NWSLC-7Y.	1.00	25.40	2.20	55.88	1.10	27.94	.48	12.19	.48	12.19	1	10

Order number of cassettes required.

Non-Laminated Label Cassettes



- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Perforated labels can be used as full-size or half-size markers
- Non-laminated adhesive labels for wire/cable identification

Part Number	Part Description	Height		Length		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	Ft.	m		

Continuous

T050X000CBC-BK	White, vinyl cloth tape.	.50	12.70	12.5	3.8	1	10
T100X000CBC-BK	White, vinyl cloth tape.	1.00	25.40	12.5	3.8	1	10

Part Number	Part Description	Width		Length		Min. Cable O.D.		Max. Cable O.D.		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		

Die-Cut

N050X075CBC	White, perforated vinyl cloth label for 18 – 14 AWG wires, 125/cassette.	.50	12.70	.75	19.05	.24	6.10	.51	12.95	1	10
N050X150CBC	White, perforated vinyl cloth label for Category 5e/Category 6 cable, 75/cassette.	.50	12.70	1.50	38.10	.48	12.19	1.02	25.91	1	10
N100X125CBC	White, perforated vinyl cloth label for 12 – 10 AWG wires, 75/cassette.	1.00	25.40	1.25	31.75	.40	10.16	.85	21.59	1	10
N100X150CBC	White, vinyl cloth label for Category 5e/Category 6 cable, 75/cassette.	1.00	25.40	1.50	38.10	.48	12.19	1.02	25.91	1	10
N100X175CBC	White, perforated vinyl cloth label for 8 – 4 AWG wires, 50/cassette.	1.00	25.40	1.75	44.45	.56	14.22	1.19	30.23	1	10

Order number of cassettes required.

Heat Shrink Label Cassettes



- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Meets print performance requirements of MIL-M-81531 and MIL-STD-202F Method 215A, Solution A, C, and D
- Meets UL Standard 224 for flammability
- Shrink ratio 3:1
- Non-adhesive flattened heat shrinkable polyolefin for wire/cable identification

Part Number	Part Description	Width		Length		Min. Cable Diameter		Max. Cable Diameter		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	Ft.	m	In.	mm	In.	mm		
Continuous											
H000X025H1C*	White, 1/8" diameter heat shrinkable polyolefin, 22 – 16 AWG.	.25	6.35	8.0	2.44	.04	1.02	.13	3.30	1	10
H000X034H1C*	White, 3/16" diameter heat shrinkable polyolefin, 18 – 12 AWG.	.34	8.64	8.0	2.44	.06	1.52	.19	4.83	1	10
H000X044H1C*	White, 1/4" diameter heat shrinkable polyolefin, 16 – 10 AWG.	.44	11.18	6.0	1.83	.08	2.03	.25	6.35	1	10
H000X084H1C*	White, 1/2" diameter heat shrinkable polyolefin, 8 – 1 AWG.	.84	21.34	6.0	1.83	.17	4.32	.50	12.70	1	10

Part Number	Part Description	Width		Length		Min. Cable Diameter		Max. Cable Diameter		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm	In.	mm	In.	mm		
Die-Cut											
H100X025H1C*	White, 1/8" diameter heat shrinkable polyolefin, 22 – 16 AWG, 100/cassette.	.25	6.35	1.00	25.40	.04	1.02	.13	3.30	1	10
H100X034H1C*	White, 3/16" diameter heat shrinkable polyolefin, 18 – 12 AWG, 100/cassette.	.34	8.64	1.00	25.40	.06	1.52	.19	4.83	1	10
H100X044H1C*	White, 1/4" diameter heat shrinkable polyolefin, 16 – 10 AWG, 100/cassette.	.44	11.18	1.00	25.40	.08	2.03	.25	6.35	1	10
H100X084H1C*	White, 1/2" diameter heat shrinkable polyolefin, 8 – 1 AWG, 75/cassette.	.84	21.34	1.00	25.40	.17	4.32	.50	12.70	1	10

*Available in yellow, replace H1C suffix with H2C.
Order number of cassettes required.

General Component Label Cassettes




- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Multi-purpose labels for identifying flat surfaces such as components, control panels, circuit boards and general labeling
- Die-cut labels designed to provide maximum aesthetic quality and appearance
- Available in adhesive polyester and vinyl cloth materials

Part Number	Part Description	Width		Height		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm		
C060X020YJC	White, polyester label, 750/cassette.	.60	15.24	.20	5.08	1	10
C100X025YJC	White, polyester label, 500/cassette.	1.00	25.40	.25	6.35	1	10
C100X050CBC	White, vinyl cloth label, 175/cassette.	1.00	25.40	.50	12.70	1	10
C100X050YJC	White, polyester label, 500/cassette.	1.00	25.40	.50	12.70	1	10
C100X050YMC	Silver, polyester label, 500/cassette.	1.00	25.40	.50	12.70	1	10
C150X075YJC	White, polyester label, 250/cassette.	1.50	38.10	.75	19.05	1	10
C200X050CBC	White, vinyl cloth label, 50/cassette.	2.00	50.80	.50	12.70	1	10
C200X050YJC	White, polyester label, 200/cassette.	2.00	50.80	.50	12.70	1	10
C200X100YJC	White, polyester label, 200/cassette.	2.00	50.80	1.00	25.40	1	10
C200X100YMC	Silver, polyester label, 150/cassette.	2.00	50.80	1.00	25.40	1	10

Order number of cassettes required.

ULTIMATE ID™ Network Label Cassette

- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Label cassettes designed for use with ULTIMATE ID® Faceplates, Patch Panels, Marker Ties, Modular Furniture Faceplates and Surface Mount Boxes
- Labels assist in the compliance of TIA/EIA-606-A labeling standard
- Available in non-adhesive polyester material




Part Number	Description	Height		Length		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	Ft.	m		
UMLS8BW	White, non-adhesive polyester label cassette.	.236	6.0	25.0	7.6	1	10

Order number of cassettes required.
For complete ULTIMATE ID® Network Labeling System product information visit www.panduit.com.

Network Component Label Cassettes

- To find the suggested label solutions for a specific network component, refer to the PAN-NET® Network Solutions catalog available online at <http://www.panduit.com/ncg1> and search by network component part number using the find function
- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Use for identifying patch panels, faceplates, punchdown blocks and other network systems hardware
- Die-cut labels designed to provide maximum aesthetic quality and appearance
- Available in adhesive polyolefin and non-adhesive polyester materials




Part Number	Part Description	Width		Height		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	In.	mm		
C061X030FJC	White, polyolefin label, 500/cassette, 1-port identifier.	.61	15.49	.30	7.62	1	10
C125X030FJC	White, polyolefin label, 200/cassette, 2-port identifier.	1.25	31.75	.30	7.62	1	10
C138X019FJC	White, polyolefin label, 200/cassette, module.	1.38	35.05	.19	4.83	1	10
C188X030FJC	White, polyolefin label, 150/cassette, 3-port identifier.	1.88	47.75	.30	7.62	1	10
C195X040Y1C	White, non-adhesive polyester label, 100/cassette, single-gang faceplate.	1.95	49.53	.40	10.16	1	10
C200X100FJC	White, polyolefin label, 150/cassette, SLCT.	2.00	50.80	1.00	25.40	1	10
C252X030FJC	White, polyolefin label, 125/cassette, 4-port identifier.	2.52	64.01	.30	7.62	1	10
C261X030FJC	White, polyolefin label, 125/cassette, 4-port identifier.	2.61	66.29	.30	7.62	1	10
C261X035Y1C	White, non-adhesive polyester label, 75/cassette, 4-port identifier.	2.61	66.29	.35	8.89	1	10
C282X030Y1C	White, non-adhesive polyester label, 75/cassette, 4-port identifier.	2.82	71.63	.30	7.62	1	10
C288X040Y1C	White, non-adhesive polyester label, 75/cassette, double-gang faceplate.	2.88	73.15	.40	10.16	1	10
C315X030FJC	White, polyolefin label, 100/cassette, 5-port identifier.	3.15	80.01	.30	7.62	1	10
C379X030FJC	White, polyolefin label, 75/cassette, 6-port identifier.	3.79	96.27	.30	7.62	1	10
C390X030Y1C	White, non-adhesive polyester label, 50/cassette, 6-port identifier.	3.90	99.06	.30	7.62	1	10
C750X050Y1C	White, non-adhesive polyester label, 30/cassette, 110 block.	7.50	190.50	.50	12.70	1	10
C788X050Y1C	White, non-adhesive polyester label, 30/cassette, GP6™ system.	7.88	200.15	.50	12.70	1	10

Order number of cassettes required.

*To find the suggested label solutions for a specific network component, refer to the PAN-NET® Network Solutions catalog available online at <http://www.panduit.com/ncg1> and search by network component part number using the find function.

Continuous Terminal Block Label Cassettes

- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Print terminal block labels ranging in size from .24 inches to .38 inches wide
- Available in continuous adhesive polyolefin tape




Part Number	Description	Height		Length		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	Ft.	m		
T024X000FJC-BK	Black on white, polyolefin tape.	.24	6.10	25.0	7.6	1	10
T031X000FJC-BK	Black on white, polyolefin tape.	.31	7.87	25.0	7.6	1	10
T038X000FJC-BK	Black on white, polyolefin tape.	.38	9.65	25.0	7.6	1	10

Order number of cassettes required.

Continuous Tape Cassettes

- P1™ Label Cassette contains an integrated memory device for automatic formatting, recall of last legend used, and number of labels remaining in the cassette
- Fast loading label cassette includes both label material and ribbon to make changing labels easy
- Print custom pipe markers, voltage markers, signs, bin markers and network identification labels on demand
- Available in a variety of colors, widths, and adhesive materials including continuous polyolefin, polyester, and vinyl
- For flat label applications only



Part Number	Part Description	Height		Length		Std. Pkg. Qty.	Std. Ctn. Qty.
		In.	mm	Ft.	m		
T019X000FJC-BK	Black on white, polyolefin MINI-COM® Module label tape.	.19	4.83	25.0	7.6	1	10
T038X000VPC-BK	Black on white, vinyl tape.	.38	9.65	25.0	7.6	1	10
T038X000VYC-WH	White on black, vinyl tape.	.38	9.65	25.0	7.6	1	10
T038X000YKC-BK	Black on clear, polyester tape.	.38	9.65	25.0	7.6	1	10
T050X000VPC-BK	Black on white, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VQC-BK	Black on blue, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VQC-WH	White on blue, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VSC-BK	Black on green, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VSC-WH	White on green, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VUC-BK	Black on orange, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VWC-BK	Black on red, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VWC-WH	White on red, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VXC-BK	Black on yellow, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000VYC-WH	White on black, vinyl tape.	.50	12.70	25.0	7.6	1	10
T050X000YKC-BK	Black on clear, polyester tape.	.50	12.70	25.0	7.6	1	10
T050X000YKC-WH	White on clear, polyester tape.	.50	12.70	25.0	7.6	1	10
T075X000VPC-BK	Black on white, vinyl tape.	.75	19.05	25.0	7.6	1	10
T075X000YKC-BK	Black on clear, polyester tape.	.75	19.05	25.0	7.6	1	10
T100X000VPC-BK	Black on white, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VQC-BK	Black on blue, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VQC-WH	White on blue, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VSC-BK	Black on green, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VSC-WH	White on green, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VUC-BK	Black on orange, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VUC-WH	White on orange, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VWC-BK	Black on red, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VWC-WH	White on red, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VXC-BK	Black on yellow, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VXC-WH	White on yellow, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000VYC-WH	White on black, vinyl tape.	1.00	25.40	25.0	7.6	1	10
T100X000YKC-BK	Black on clear, polyester tape.	1.00	25.40	25.0	7.6	1	10
T100X000YKC-WH	White on clear, polyester tape.	1.00	25.40	25.0	7.6	1	10

Material Selection Guide

Material Type	Temperature Range	Description	Color(s)	Outdoor Rated	UL Recognized	RoHS Compliant‡
Heat Shrinkable Polyolefin, Non-Adhesive^	-67°F to 275°F (-55°C to 135°C)	Polyolefin heat shrink for wire and cable marking applications.	White Yellow	Yes	UL 224	Yes
Polyester, Adhesive	-40°F to 257°F (-40°C to 125°C)	General purpose material for component labeling; does not stretch or easily tear.	Clear	Yes	UL 969	Yes
			Silver	Yes	UL 969	Yes
			White	Yes	UL 969	Yes
Polyester, Non-Adhesive	-10°F to 150°F (-23°C to 66°C)	Non-adhesive material ideal for network systems labeling; provides durability, high temperature resistance, and dimensional stability.	White	Yes	No	Yes
Polyolefin, Adhesive	-50°F to 120°F (-46°C to 49°C)	Durable, pliable material with permanent adhesive for terminal block and network component labels.	White	No	UL 969	Yes
Self-Laminating Vinyl, Adhesive	-40°F to 150°F (-40°C to 66°C)	Self-laminating film for most general wire and cable labeling; conformable material.	White Blue Green Red Yellow Print-On	Yes	UL 969	Yes
Vinyl Cloth, Adhesive	-50°F to 170°F (-46°C to 77°C)	General purpose material, vinyl impregnated cloth resists oil and abrasion; material can be removed, repositioned, and reused.	White	No	UL 969	Yes
Vinyl, Adhesive	-40°F to 176°F (-40°C to 80°C)	General purpose material for pipe marking, bin marking, and facility identification; conformable material for flat applications.	White Black Blue Green Orange Red Yellow	Yes	UL 969	Yes

^Product meets print performance requirements of MIL-M-81531 and MIL-STD-202F Method 215A, Solution A, C, and D.
‡Material is RoHS compliant per European Directive 2002/95/EC on the Restriction of Hazardous Substances (RoHS).

Related Products

EASY-MARK™ Labeling Software



PROG-EMCD3

- EASY-MARK™ Labeling Software simplifies label creation for the specific needs of your applications
- Instructions and user interface are available in English, French, German, Italian, Spanish, Korean, Chinese and Portuguese
- Intuitive interview process allows automatic generation of compliant labels and signs
- Software selects and formats the optimum label for your specific project
- **WYSIWYG** (What You See Is What You Get) user interface, alpha/numeric serialization, data import, symbol import

System Requirements:

WINDOWS^ 2000, WINDOWS^ NT4.x, WINDOWS^ XP or WINDOWS^ Vista; 64MB hard drive space and 64 MB RAM (256MB RAM Recommended)

^WINDOWS is a registered trademarks of Microsoft Corporation in the United States and/or other countries.

WORLDWIDE SUBSIDIARIES AND SALES OFFICES

PANDUIT CANADA
Markham, Ontario
cs-cdn@panduit.com
Phone: 800.777.3300

PANDUIT EUROPE LTD.
London, UK
cs-emea@panduit.com
Phone: 44.20.8601.7200

PANDUIT SINGAPORE PTE. LTD.
Republic of Singapore
cs-ap@panduit.com
Phone: 65.6305.7575

PANDUIT JAPAN
Tokyo, Japan
cs-japan@panduit.com
Phone: 81.3.3767.7011

PANDUIT LATIN AMERICA
Jalisco, Mexico
cs-la@panduit.com
Phone: 52.333.777.6000

PANDUIT AUSTRALIA PTY. LTD.
Victoria, Australia
cs-aus@panduit.com
Phone: 61.3.9794.9020

For a copy of PANDUIT product warranties, log on to www.panduit.com/warranty



For more information
Visit us at www.panduit.com

Contact Customer Service by email: cs@panduit.com
or by phone: 800-777-3300 and reference IDCB41

©2007 PANDUIT Corp.
ALL RIGHTS RESERVED.
Printed in U.S.A.
Replaces SA-IDCB22
Product Bulletin Number SA-IDCB41
9/2007